

























لیست قیمت و موجودی تجهیزات حفاظتی تحت شبکه ورتینا

MODEL	PICTURE	MP	DESCRIPTION	
VE-1122N-IR		2MP	1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, IK10, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Base bracket: metal Cover: plastic	24,500,000
VNC-5225N		2MP	1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by <b>Darkfighter Ultra-low light</b> technology, Color: 0.005 lux @(F1.2, AGC ON), 0 lux with IR; 25fps/30fps(1920x1080); 2.8/4/6mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, <b>Smart Series</b>	CALL
VNC-5265		2MP	1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by <b>Darkfighter Ultra-low light</b> technology, Color: 0.005 lux @(F1.2, AGC ON), 0 lux with IR; 25fps/30fps(1920x1080); 2.8/4/6mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, <b>Smart Series</b>	CALL
VNC-2230		2MP	1/3" Progressive CMOS, ICR, 0 lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, <b>WDR</b> , 3D DNR, BLC, Intrusion Detection, Line Crossing Detection, IR: up to 30m, On-board card slot (up to 64GB)	44,000,000
VNC-4360		3MP	1/3" Progressive CMOS, ICR, 0lux with IR, 2048x1536:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 10m, On-board card slot (up to 64GB)	30,000,000
VNC-2361		3MP	1/3" Progressive CMOS, ICR, 2304x1296:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Eyeball: Metal Cover: Plastic	27,000,000
VNC-2331		3MP	1/3" Progressive CMOS, ICR, 2304x1296:20fps, 2.8~12mm Vari-Focal lens, H.264+&H.264, IP67, <b>120db WDR</b> , 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring, Full metal	CALL
VNC-2371		3MP	1/3" Progressive CMOS, ICR, 2304x1296:20fps, 2.8~12mm VF lens, H.264+&H.264, IP67, IK10, <b>120db WDR</b> , 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring, Full metal	CALL
<p>WHATSAPP: ۰۹۳۶۴۹۰۹۳۵۵      TEL: ۰۷۱۳۲۳۴۰۵۱۵      WWW.HEFAZATIP.COM</p>				

لیست قیمت تجهیزات حفاظتی تحت شبکه ورتینا (ویژه مرداد ۱۳۹۹)

MODEL	PICTURE	MP	DESCRIPTION	
VE-1542-IR		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Front cover(black part): metal Back cover & Bracket(white part): Full Metal	35,000,000
VE-1142N-IR		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Front cover(black part): metal Back cover & Bracket(white part): Full Metal	37,000,000
VNC-2461		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Eyeball: Metal, Cover: Plastic	29,000,000
VNC-2431		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8~12mm VF lens, H.264+&H.264, IP67, 120db WDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring, Full metal	CALL
VNC-4430		4MP	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 2.8~12mm Vari-Focal lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120db WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 64GB (SD card not included), H.264+ Optimized Codec, Professional Series	CALL
VNC-2471		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8~12mm VF lens, H.264+&H.264, IP67, IK10, 120db WDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring, Full metal	CALL
VNC-4190		1MP	1/4" Progressive CMOS, H.264, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100db WDR, 3D DNR, BLC,	CALL
VNC-6640S		6MP	1/2" Progressive CMOS, H.264, Fish eye, ICR, 0lux with IR, Up to 3072 x 2048 resolution, 1.05mm/F2.8 lens, 360°Panoramic view, H.264/MJPEG, dual-stream, DC12V & PoE, Support on-board storage, Up to 15m IR, Audio/Alarm IO	CALL
<div> <div>WHATSAPP: ۰۹۳۶۴۹۰۹۳۵۵</div> <div>۰۷۱۳۲۳۴۰۵۱۵</div> <div>WWW.HEFAZATIP.COM</div> </div>				











لیست قیمت تجهیزات حفاظتی تحت شبکه ورتینا (ویژه مرداد ۱۳۹۹)

MODEL	PICTURE	MP	DESCRIPTION	
VNC-5525N		5MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux, 0 lux with IR; 20fps(2560×1920), 25fps/30fps(2560×1440, 2048×1536, 1920×1080); 2.8/4/6/12mm lens optional; <b>120dB WDR; VCA functions</b> ; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0; up to <b>80m IR distance</b> , All-metal housing, IP67; DC12V&PoE; SD/SDHC/SDXC slot, up too, <b>Smart Series</b>	CALL
SNC-4522		5MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux, 0 lux with IR; 20fps(2560×1920), 25fps/30fps(2560×1440, 2048×1536, 1920×1080); 2.8/4/6/12mm lens optional; <b>120dB WDR; VCA functions</b> ; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0; up to <b>80m IR distance</b> , All-metal housing, IP67; DC12V&PoE; SD/SDHC/SDXC slot, up too, <b>Smart Series</b>	CALL
VNC-5535SN		5MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux, 0 lux with IR; 20fps(2560×1920), 25fps/30fps(2560×1440, 2048×1536, 1920×1080); 2.8~12mm motorized VF lens; <b>120dB WDR; VCA functions</b> ; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 50m IR distance; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, S model: Audio/Alarm IO, <b>Smart Series</b>	CALL
VNC-5575SN		5MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(2560×1920), 25fps/30fps(2560×1440, 2048×1536, 1920×1080); 2.8~12mm motorized VF lens; <b>120dB WDR; VCA functions</b> ; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67, IK8; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, S model: Audio/Alarm IO, Line crossing detection, Intrusion dete, <b>Smart Series</b>	CALL
VNC-5826		8MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps(2560×1920, 2560×1440, 2048×1536, 1920×1080); 2.8/4/6/12mm lens optional; 120dB WDR; <b>VCA functions</b> ; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, <b>up to 80m IR distance</b> , Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, <b>4K smart Camera</b>	CALL
VNC-6225S		2MP	<b>License Plate Recognition, Darkfighter ultra-low light</b> technology, 1/1.8" progressive scan CMOS sensor, Full HD1080p, up to 60fps, 120dB WDR, Full smart feature-set, Motorized lens with Smart Focus, Up to 128GB on-board storage, Up to 50m IR range, IP67	CALL
VNC-6226S		2MP	<b>License Plate Recognition, Darkfighter ultra-low light</b> technology, 1/1.8" progressive scan CMOS sensor, Full HD1080p, up to 60fps, 120dB WDR, Full smart feature-set, Visible Light, Motorized lens with Smart Focus, Up to 128GB on-board storage, Up to 50m IR range, IP67	CALL
VNC-5230		2MP	<b>Darkfighter Ultra-low light</b> technology, 1/1.8" Progressive Scan CMOS, ICR, 0 lux with IR, Slow shutter, 1920x1080: 50/60fps, 2.8~12mm/F1.4 Motorized VF lens with Smart Focus, H.264/MPEG4, Triple-Stream, Support SD/SDXC Card up to 128GB, IP67, DC12V/PoE, up to 50m IR range, Bracket & junction box included, - S: Audio/Alarm IO, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, Poepple count, , <b>Smart Series</b>	CALL
<p>WHATSAPP: ۰۹۳۶۴۹۰۹۳۵۵      TEL: ۰۷۱۳۲۳۴۰۵۱۵      WWW.HEFAZATIP.COM</p>				

لیست قیمت تجهیزات حفاظتی تحت شبکه ورتینا (ویژه مرداد ۱۳۹۹)








MODEL	PICTURE	MP	DESCRIPTION	
VNC-2280N		2MP	2MP, 1/3" CMOS, H.265+/H.265/H.264+/H.264/MJPEG, 3D DNR, ICR, Color: 0.05lux/F2.0, B/W:0.01lux/F2.0, Zoom: 4x, Angle of View: 80-64.5 degree (Wide~Tele), Digital Zoom:16X, 1920x1080:30fps, Pan range:0°~350°; Tilt range: 0°~90°(Auto Flip), Pan Speed: 0.1° -100°/s, Tilt Speed: 0.1° -80°/s, 30m IR, POE&12VDC,	CALL
VNC-4285N		2MP	2MP, 1/2.8" CMOS, H.265+/H.265/H.264+/H.264/MJPEG, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:12X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, <b>150m IR Distance</b>	CALL
VNC-5880		8MP	<b>8MP PTZ</b> , 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:36x, Focus:4.3-129.0mm, Digital Zoom:12X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, <b>200m IR Distance</b>	CALL
VNC-6280		16MP	<b>16MP PTZ</b> , 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:36x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s, <b>150m IR Distance</b>	CALL
VHN-K130		Multi	Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video stream decoding, USB 2.0 interface for video backup, 256 units of DVR and SeedDome	CALL
VCU-1200		Multi	<ul style="list-style-type: none"><li>• Control up to 255 PTZ cameras</li><li>• Superior system compatibility : Multi protocols support</li><li>• OSD menu • 3D joystick control</li><li>• Control up to 255 PTZ cameras</li></ul>	50,000,000
VPS-8100		1.8 Gbps switching fabric	IEEE 802.3at and IEEE 802.3af Power over Ethernet (PoE) compliant , Supports PoE power up to 123W for all PoE ports (8 port) and 230W for (16 port) ,4 kV surge protection for PoE ports , IEEE 802.3x flow control support , Plug-and-play installation , 1.8 Gbps switching fabric (8 port) and 7.2 Gbps switching fabric , 1.25 & 2.75 Mbits RAM Data Buffer , Sturdy metal enclosure, 30 watts per PoE	CALL
VPS-16100		7.2 Gbps switching fabric		CALL
VPS-24100		8.8 Gbps switching fabric		CALL
WHATSAPP:۰۹۳۶۴۹۰۹۳۵۵      TEL:۰۷۱۳۲۳۴۰۵۱۵      WWW.HEFAZATIP.COM				

لیست قیمت تجهیزات حفاظتی تحت شبکه ورتینا (ویژه مرداد ۱۳۹۹)

MODEL	PICTURE	DESCRIPTION	
VNR-405		40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920×1080P resolution , Support network detection, including network delay, packet loss, etc	23,000,000
VNR-405P		40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, <b>4 independent network POE</b> interfaces for built-in switch, 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920×1080P resolution , Support network detection, including network delay, packet loss, etc	36,000,000
VNR-805		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920×1080P resolution , Support network detection, including network delay, packet loss, etc	33,500,000
VNR-805E		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent network interfaces for built-in switch, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920×1080P resolution , Support network detection, including network delay, packet loss, etc	43,700,000
VNR-805P		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, <b>8 independent network POE</b> interfaces for built-in switch, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920×1080P resolution , Support network detection, including network delay, packet loss, etc	53,700,000
VNR-808		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 8 Megapixels resolution recording , HDMI and VGA output at up to 1920×1080P resolution , Support network detection, including network delay, packet loss, etc	35,000,000
VNR-1605		160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920×1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc	38,700,000
VNR-1605E		160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 8 independent network interfaces for built-in switch, 380 1U case , Third-party network cameras supported , HDMI and VGA output at up to 1920×1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc	56,000,000
VNR-1605P		160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, <b>16 independent network POE</b> interfaces for built-in switch, 380 1U case , Third-party network cameras supported , HDMI and VGA output at up to 1920×1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc	70,000,000
Vertia 3500+ ServerStation		• 32 Channel connected cameras • Central management system • Supports GPU hardware decoding to save CPU resources • Windows Embedded System 7 • Storage 4 HDDs connectable • Third-party product integration via ONVIF • Decoding performance 2*4K / 9 * 1080p	CALL
<p>WHATSAPP: ۰۹۳۶۴۹۰۹۳۵۵      TEL: ۰۷۱۳۲۳۴۰۵۱۵      WWW.HEFAZATIP.COM</p>			



## لیست قیمت و موجودی تجهیزات حفاظتی تحت شبکه اسپرادو

MODEL	PICTURE	MP	DESCRIPTION	
SNC-4222		2MP	1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67,IK10, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring, Base bracket: metal Cover: plastic	24,500,000
SNC-4422		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring, Front cover(black part): metal Back cover & Bracket(white part): Full Metal	35,000,000
SNC-6222		2MP	1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67,IK10, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring, Base bracket: metal Cover: plastic	26,500,000
SNC-6422		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring, Front cover(black part): metal Back cover & Bracket(white part): Full Metal	37,000,000
MODEL	PICTURE	DESCRIPTION		
SNS-5608		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920×1080P resolution , Support network detection, including network delay, packet loss, etc		33,500,000
SNS-5616		160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920×1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc		38,700,000
SNS-5816		160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920×1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc		42,000,000
WHATSAAPP:۰۹۳۶۴۹۰۹۳۵۵      TEL:۰۷۱۳۲۳۴۰۵۱۵      WWW.HEFAZATIP.COM				